

## Hongshang

### H-2(3X)

Thin-wall heat shrink tubing / flexible / flame retardant / 3:1

#### Features:

- Crosslinked Polyolefin
- Shrink ratio: 3:1
- Flame retardant
- General purpose
- High flexibility

#### Approvals:

- UL224 125 °C VW-1 600 V file E204071
- CSA file no.: 1934614
- Meets: RoHS, Sony-SS-00259

#### Application:

- Operating temperature: -55 °C to +125 °C
- Minimum shrink temperature: +70 °C
- Minimum full recovery temperature: +100 °C
- Longitudinal change: 0 ± 10% max.

#### Order information:

- Color: black
- Other colors: red, blue, yellow, green, white, brown, orange, purple, grey (flame retardant class 2)

Type / Size	As supplied: inside diameter in mm (min)	After recovery: inside diameter in mm (max)	After recovery: wall thickness in mm (min)	Reel / Meter
H-2(3X) 1,5 / 0,5	1,5	0,5	0,45	150
H-2(3X) 3,0 / 1,0	3,0	1,0	0,55	150
H-2(3X) 4,5 / 1,5	4,8	1,5	0,60	75
H-2(3X) 6,0 / 2,0	6,4	2,0	0,65	75
H-2(3X) 9,0 / 3,0	9,5	3,0	0,75	75
H-2(3X) 12,0 / 4,0	12,7	4,0	0,80	50
H-2(3X) 18,0 / 6,0	19,1	6,0	0,90	30
H-2(3X) 24,0 / 8,0	25,4	8,0	1,00	30
H-2(3X) 39,0 / 13,0	39,0	13,0	1,25	30