

## Hongshang

### H-2F(3X)

Thin-wall heat shrink tubing / flexible / flame retardant / 3:1 / mil spec 135 degrees

#### Features:

- Crosslinked Polyolefin
- Shrink ratio: 3:1
- Flame retardant
- High flexibility

#### Approvals:

- UL224 125 °C VW-1 600 V file E204071
- CSA file no.: 1934614
- Meets: RoHS
- Meets: SAE-AMS-DTL-23053/5 class 1 and 2

#### Application:

- Operating temperature: -55 °C to +135 °C
- Minimum shrink temperature: +70 °C
- Minimum full recovery temperature: +100 °C
- Longitudinal change: 0 ± 10% max.

#### Order information:

- Color: black
- Other colors: red, blue, yellow, green, white (flame retardant class 1). Transparent (class 2, not flame retardant)

Type / Size	As supplied: inside diameter in mm (min)	After recovery: inside diameter in mm (max)	After recovery: wall thickness in mm (min)	Reel / Meter
H-2F(3X) 1,5/0,5	1,5	0,5	0,45	150
H-2F(3X) 3,0/1,0	3	1	0,55	150
H-2F(3X) 4,5/1,5	4,8	1,5	0,6	75
H-2F(3X) 6,0/2,0	6,4	2	0,65	75
H-2F(3X) 9,0/3,0	9,5	3	0,75	75
H-2F(3X) 12,0/4,0	12,7	4	0,8	50
H-2F(3X) 18,0/6,0	19,1	6	0,9	30
H-2F(3X) 24,0/8,0	25,4	8	1,2	30
H-2F(3X) 39,0/13,0	39	13	1,25	30