

## Hongshang

### H-2(HF)

Thin-wall heat shrink tubing / flexible / flame retardant / 2:1 / halogen free

#### Features:

- Crosslinked Polyolefin
- Shrink ratio: 2:1
- Flame retardant
- Halogen free
- Low smoke emission

#### Approvals:

- UL224 125 °C VW-1 600 V
- Meets: RoHS

#### Application:

- Operating temperature: -55 °C to +125 °C
- Minimum shrink temperature: +70 °C
- Minimum full recovery temperature: +100 °C
- Longitudinal change: 0 ± 10% max.

#### Order information:

- Colors: black and white
- Other colors are available on request

Type / Size	As supplied: inside diameter in mm (min)	After recovery: inside diameter in mm (max)	After recovery: wall thickness in mm (min)	Reel / Meter
H-2(HF) 1,2/0,6	1,2	0,6	0,33	300
H-2(HF) 1,6/0,8	1,6	0,8	0,36	300
H-2(HF) 2,4/1,2	2,4	1,2	0,44	300
H-2(HF) 3,2/1,6	3,2	1,6	0,44	300
H-2(HF) 4,8/2,4	4,8	2,4	0,51	150
H-2(HF) 6,4/3,2	6,4	3,2	0,56	150
H-2(HF) 9,5/4,8	9,5	4,8	0,56	75
H-2(HF) 12,7/6,4	12,7	6,4	0,65	75
H-2(HF) 16,0/8,0	16,0	8,0	0,69	75
H-2(HF) 19,0/9,5	19,0	9,5	0,80	50
H-2(HF) 25,4/12,7	25,4	12,7	0,90	50
H-2(HF) 32,0/16,0	32,0	16,0	1,02	30
H-2(HF) 38,1/19,0	38,1	19,0	1,02	30
H-2(HF) 50,8/25,4	50,8	25,4	1,14	30
H-2(HF) 76,2/38,1	76,2	38,1	1,27	30