

Hongshang

H-2F(Y/G)

Thin-wall heat shrink tubing / yellow/green striped / flexible / flame retardant / 2:1/3:1 / mil spec 135 degrees

Features:

- Crosslinked Polyolefin
- Shrink ratio: 2:1 and 3:1
- Flame retardant
- High flexibility

Approvals:

- UL224 125 °C VW-1 600 V file E204071
- CSA file no.: 1934614
- Meets: RoHS
- Meets: SAE-AMS-DTL-23053/5 class 1

Application:

- Operating temperature: -55 °C to +135 °C
- Minimum shrink temperature: +70 °C
- Minimum full recovery temperature: +100 °C
- Longitudinal change: 0 ± 10% max.

Order information:

- Color: yellow / green
- Also available in various lengths and in mini boxes

Type / Size	As supplied: inside diameter in mm (min)	After recovery: inside diameter in mm (max)	After recovery: wall thickness in mm (min)	Reel / Meter
H-2F(Y/G) 2:1 1,6/0,8	1,6	0,8	0,32	150
H-2F(Y/G) 2:1 2,4/1,2	2,4	1,2	0,42	150
H-2F(Y/G) 2:1 3,2/1,6	3,2	1,6	0,42	150
H-2F(Y/G) 2:1 4,8/2,4	4,8	2,4	0,52	75
H-2F(Y/G) 2:1 6,4/3,2	6,4	3,2	0,54	75
H-2F(Y/G) 2:1 9,5/4,8	9,5	4,8	0,54	75
H-2F(Y/G) 2:1 12,7/6,4	12,7	6,4	0,62	50
H-2F(Y/G) 2:1 16,0/8,0	16,0	8,0	0,67	50
H-2F(Y/G) 2:1 19,0/9,5	19,0	9,5	0,75	30
H-2F(Y/G) 2:1 25,4/12,7	25,4	12,7	0,85	30
H-2F(Y/G) 2:1 32,0/16,0	32,0	16,0	0,85	30
H-2F(Y/G) 2:1 38,1/19,0	38,1	19,0	0,96	30
H-2F(Y/G) 2:1 50,8/25,4	50,8	25,4	0,96	30
H-2F(Y/G) 2:1 76,2/38,1	76,2	38,1	1,17	15
H-2F(Y/G) 2:1 102,0/50,8	102,0	50,8	1,30	15