

Hongshang

H-1

Thin-wall heat shrink tubing / non flame retardant / 2:1

Features:

- Crosslinked Polyolefin
- Shrink ratio: 2:1
- 100% transparent
- Bright shiny-black

Approvals:

- Meets: RoHS

Application:

- Operating temperature: -55 °C to +105 °C
- Minimum shrink temperature: +70 °C
- Minimum full recovery temperature: +95 °C
- Longitudinal change: 0 ± 10% max.

Order information:

- Colors: shiny-black / transparent
- Also available in various lengths and in mini boxes

Type / Size	As supplied: inside diameter in mm (min)	After recovery: inside diameter in mm (max)	After recovery: wall thickness in mm (min)	Reel / Meter
H-1 1,2/0,6	1,2	0,6	0,33	150
H-1 1,6/0,8	1,6	0,8	0,36	150
H-1 2,4/1,2	2,4	1,2	0,44	150
H-1 3,2/1,6	3,2	1,6	0,44	150
H-1 4,8/2,4	4,8	2,4	0,56	75
H-1 6,4/3,2	6,4	3,2	0,56	75
H-1 9,5/4,8	9,5	4,8	0,56	75
H-1 12,7/6,4	12,7	6,4	0,65	50
H-1 16,0/8,0	16,0	8,0	0,69	50
H-1 19,0/9,5	19,0	9,5	0,80	30
H-1 25,4/12,7	25,4	12,7	0,90	30
H-1 32,0/16,0	32,0	16,0	0,90	30
H-1 38,1/19,0	38,1	19,0	1,00	30
H-1 50,8/25,4	50,8	25,4	1,00	30
H-1 76,2/38,1	76,2	38,1	1,20	15