

Hongshang

H-5(3X)-F and H-5(4X)-F

Dual-wall heat shrink tubing / flexible / flame retardant / 3:1/4:1 / adhesive lined

Features:

- Crosslinked co-extruded adhesive lined Polyolefin
- Shrink ratio: 3:1 and 4:1
- Flame retardant
- Excellent sealing and insulation properties
- UV resistant

Approvals:

- UL224 125 °C VW-1 600 V file E204071
- Meets: RoHS
- Meets: SAE-AMS-DTL-23053/4

Application:

- Operating temperature: -55 °C to +125 °C
- Minimum shrink temperature: +70 °C
- Minimum full recovery temperature: +110 °C
- Longitudinal change: 0 ± 10% max.

Order information:

- Color: black
- Other colors: red, blue, yellow, green, white (flame retardant class 2)
- Also available in various lengths and in mini boxes (please see page 69)

Type / Size	As supplied: inside diameter in mm (min)	After recovery: inside diameter in mm (max)	After recovery: wall thickness in mm (min)	Reel / Meter
H-5(3X)-F 3:1 3,0/1,0	3,0	1,0	1,00	150
H-5(3X)-F 3:1 4,8/1,5	4,8	1,5	1,00	75
H-5(3X)-F 3:1 6,0/2,0	6,0	2,0	1,00	75
H-5(3X)-F 3:1 9,0/3,0	9,0	3,0	1,40	50
H-5(3X)-F 3:1 12,0/4,0	12,0	4,0	1,60	30
H-5(3X)-F 3:1 19,0/6,0	19,0	6,0	2,15	30
H-5(3X)-F 3:1 24,0/8,0	24,0	8,0	2,40	30
H-5(3X)-F 3:1 30,0/10,0	30,0	10,0	2,40	30
H-5(3X)-F 3:1 40,0/13,0	40,0	13,0	2,40	30