

Hongshang

H-175K

Special heat shrink tubing / Kynar® / 175 degrees / 2:1

Features:

- Crosslinked PVDF
- Shrink ratio: 2:1
- Superior mechanical and abrasion resistance
- Highly flame retardant
- High temperature resistance
- Excellent chemical and solvent resistance

Approvals:

- Meets: RoHS
- Meets: SAE-AMS-DTL-23053/18

Application:

- Operating temperature: -55 °C to +175 °C
- Minimum shrink temperature: +175 °C
- Longitudinal change: 0 ± 10% max.

Order information:

- Color: transparent (black available on request)

Type / Size	As supplied: inside diameter in mm (min)	After recovery: inside diameter in mm (max)	After recovery: wall thickness in mm (min)	Reel / Meter
H-175K 1,2/0,6	1,2	0,6	0,20	150
H-175K 1,6/0,8	1,6	0,8	0,20	150
H-175K 2,4/1,2	2,4	1,2	0,23	150
H-175K 3,2/1,6	3,2	1,6	0,23	150
H-175K 4,8/2,4	4,8	2,4	0,23	75
H-175K 6,4/3,2	6,4	3,2	0,28	75
H-175K 9,5/4,8	9,5	4,8	0,28	1,22
H-175K 12,7/6,4	12,7	6,4	0,28	1,22
H-175K 19,1/9,5	19,1	9,5	0,36	1,22
H-175K 25,4/12,7	25,4	12,7	0,41	1,22