

Hongshang

HTFE

Special heat shrink tubing / Teflon® / 260 degrees / 1,5:1

Features:

- Modified Tetrafluoroethylene
- Shrink ratio: 1,5:1
- Superior chemical and mechanical performance
- Very low friction coefficient
- Excellent electrical properties

Approvals:

- Meets: RoHS
- Meets: SAE-AMS-DTL-23053/12

Application:

- Operating temperature: -65 °C to +260 °C
- Minimum full recovery temperature: +350 °C
- Longitudinal change: 0 ± 10% max.

Order information:

- Color: transparent

Type / Size	As supplied: inside diameter in mm (min)	After recovery: inside diamter in mm (max)	After recovery: wall thickness in mm (min)	Standard length in mm
HTFE AWG 20	1,52	0,97	0,30	1220
HTFE AWG 18	1,93	1,17	0,30	1220
HTFE AWG 16	2,36	1,45	0,30	1220
HTFE AWG 14	3,05	1,82	0,30	1220
HTFE AWG 12	3,81	2,26	0,30	1220
HTFE AWG 10	4,85	2,80	0,30	1220
HTFE AWG 8	6,10	3,55	0,38	1220
HTFE AWG 6	7,67	4,40	0,38	1220
HTFE AWG 4	9,40	5,45	0,38	1220
HTFE AWG 2	10,92	6,90	0,38	1220
HTFE AWG 0	11,94	8,56	0,38	1220