

Hongshang

H-2(XT)

Special heat shrink tubing / insulation sleeve

Features:

- Crosslinked Polyolefin
- Non shrinkable
- Flame retardant

Approvals:

- Meets: RoHS
- UL224 125 °C VW-1 600 V file E204071

Application:

- Operating temperature: -55 °C to +125 °C
- Longitudinal change: 0 ± 10% max.

Order information:

- Color: black

Type / Size	As supplied: inside diameter in mm (min)	wall thickness in mm (min)	Reel / Meter
H-2(XT) AWG 18	1,00	0,4	150
H-2(XT) AWG 16	1,30	0,4	150
H-2(XT) AWG 14	1,65	0,4	150
H-2(XT) AWG 12	2,10	0,4	150
H-2(XT) AWG 10	2,60	0,5	75
H-2(XT) AWG 8	3,30	0,5	75
H-2(XT) AWG 6	4,10	0,5	75
H-2(XT) AWG 4	5,20	0,5	50
H-2(XT) AWG 2	6,50	0,5	50
H-2(XT) AWG 0	8,30	0,5	30
H-2(XT) 3/8	9,50	0,5	30
H-2(XT) 7/16	11,10	0,5	30
H-2(XT) 1/2	12,70	0,5	30