

## Hongshang

### HSTV

Medium-wall heat shrink tubing / with hot melt adhesive for CATV network

#### Features:

- Medium-wall tubing with hot melt adhesive
- With thermo-chromatic stripes / paint
- Designed for CATV industry
- Easy to remove for repairs
- UV resistant

#### Approvals:

- Meets: RoHS

#### Application:

- Operating temperature: -55 °C to +110 °C
- Minimum full recovery temperature: +120 °C
- Longitudinal change: 0 ± 10% max.

#### Order information:

- Color: black

Type / Size	As supplied: inside diameter in mm (min)	After recovery: inside diameter in mm (max)	After recovery: wall thickness in mm (min)	Standard length in mm
HRS 33/8	33,0	8,0	2,5	1220
HRS 40/12	40,0	12,0	2,5	1220
HRS 55/16	55,0	16,0	2,7	1220
HRS 65/19	65,0	19,0	2,9	1220
HRS 75/22	75,0	22,0	3,0	1220
HRS 85/25	85,0	25,0	3,0	1220
HRS 95/25	95,0	25,0	3,0	1220
HRS 115/34	115,0	34,0	3,2	1220
HRS 140/42	140,0	42,0	3,3	1220
HRS 160/50	160,0	50,0	3,3	1220
HRS 180/58	180,0	58,0	3,3	1220
HRS 200/65	200,0	65,0	3,3	1220
HRS 235/65	235,0	65,0	3,7	1220
HRS 265/75	265,0	75,0	3,8	1220
HRS 300/85	300,0	85,0	3,8	1220
HRS 350/100	350,0	100,0	4,2	1220
HRS 410/150	410,0	150,0	4,2	1000