

Hongshang

HRA-6X

Heavy-wall heat shrink tubing / with hot melt adhesive and extra high shrink ratio

Features:

- Heavy-wall tubing with hot melt adhesive
- Shrink ratio: 6:1
- Crosslinked Polyolefin
- Excellent sealing properties
- Extra heavy-wall
- UV resistant

Approvals:

- Meets: RoHS

Application:

- Operating temperature: -55 °C to +110 °C
- Minimum full recovery temperature: +120 °C
- Longitudinal change: 0 ± 10% max.

Order information:

- Color: black

Type / Size	As supplied: inside diameter in mm (min)	After recovery: inside diameter in mm (max)	After recovery: wall thickness in mm (min)	Standard length in mm
HRA-6X 19,0/3,2	19,0	3,2	3,2	1220
HRA-6X 33,0/5,5	33,0	5,5	3,4	1220
HRA-6X 44,4/7,4	44,4	7,4	3,6	1220
HRA-6X 50,8/8,3	50,8	8,3	4,7	1220
HRA-6X 69,8/11,7	69,8	11,7	4,7	1220
HRA-6X 88,9/17,1	88,9	17,1	4,7	1220
HRA-6X 119,4/22,9	119,4	22,9	4,7	1220
HRA-6X 235,0/40,0	235,0	40,0	4,7	1220