

Hongshang

HBM

Halogen free busbar insulation tubing

Features:

- Medium-wall halogen free busbar insulation tubing
- Crosslinked Polyolefin
- Excellent electrical properties and creeping resistance
- UV resistant
- Up to 36 kV

Approvals:

- Meets: RoHS

Application:

- Minimum full recovery temperature: +110 °C
- Longitudinal change: 0 ± 10% max.

Order information:

- Color: red

| Type / Size | As supplied: inside diameter in mm (min) | After recovery: inside diameter in mm (max) | After recovery: wall thickness in mm (min) | Reel / Meter & Standard length in mm |
|-------------|--|---|--|--|
| HBM 19/6 | 19,0 | 6,0 | 1,9 | 30 |
| HBM 25/10 | 25,0 | 10,0 | 1,9 | 30 |
| HBM 30/12 | 30,0 | 12,0 | 1,9 | 30 |
| HBM 35/14 | 35,0 | 14,0 | 1,9 | 30 |
| HBM 40/16 | 40,0 | 16,0 | 1,9 | 30 |
| HBM 50/20 | 50,0 | 20,0 | 1,9 | 30 |
| HBM 65/25 | 65,0 | 25,0 | 1,9 | 30 |
| HBM 75/30 | 75,0 | 30,0 | 1,9 | 15 |
| HBM 100/40 | 100,0 | 40,0 | 1,9 | 15 |
| HBM 120/50 | 120,0 | 50,0 | 2,9 | 1000 mm |
| HBM 150/60 | 150,0 | 60,0 | 2,9 | 1000 mm |
| HBM 180/60 | 180,0 | 60,0 | 2,9 | 1000 mm |
| HBM 205/75 | 205,0 | 75,0 | 2,9 | 1000 mm |