

Hongshang

HBTM and HBTH

Halogen free flexible busbar insulation tubing

Features:

- HBTM = medium-wall tubing
- HBTH = heavy-wall tubing
- Medium- and heavy-wall flexible busbar insulation tubing
- Modified Polyolefin
- Excellent electrical properties and creeping resistance
- Halogen free
- UV and weather resistant
- Up to 36 kV

Approvals:

- Meets: RoHS

Application:

- Minimum full recovery temperature: +120 °C
- Longitudinal change: 0 ± 10% max.

Order information:

- Color: red

Type / Size	As supplied: inside diameter in mm (min)	After recovery: inside diameter in mm (max)	After recovery: wall thickness in mm (min)	Reel / Meter & Standard length in mm
HBTM 15/6	15,0	6,0	2,5	30
HBTM 25/10	25,0	10,0	2,9	30
HBTM 30/12	30,0	12,0	2,9	30
HBTM 40/16	40,0	16,0	2,9	30
HBTM 50/20	50,0	20,0	2,9	15
HBTM 65/25	65,0	25,0	2,9	15
HBTM 75/30	75,0	30,0	2,9	15
HBTM 100/40	100,0	40,0	2,9	15
HBTM 120/50	120,0	50,0	2,9	15
HBTH 25/10	25,0	10,0	4,0	1220 mm
HBTH 40/16	40,0	16,0	4,0	1220 mm
HBTH 50/20	50,0	20,0	4,0	1220 mm
HBTH 75/25	75,0	25,0	4,0	1220 mm
HBTH 95/30	95,0	30,0	4,0	1220 mm
HBTH 120/40	120,0	40,0	4,1	1220 mm
HBTH 180/58	180,0	58,0	4,1	1220 mm