

Hongshang

HSEC and HCEC

Moulded parts / cable end caps with spiral adhesive coating

Features:

- HSEC = standard end cap
- HSEC-L = standard end cap, extended length
- HCEC = conductive end cap
- Crosslinked Polyolefin
- Excellent sealing properties
- Ideal for low voltage applications
- UV and weather resistant

Approvals:

- Meets: RoHS

Application:

- Operating temperature: -55 °C to +110 °C
- Minimum full recovery temperature: +120 °C
- Longitudinal change: 0 ± 10% max.

Order information:

- Color: black

| Type / Size | As supplied: inside diameter in mm (min) | After recovery: inside diameter in mm (max) | After recovery: wall thickness in mm (min) | After recovery: length in mm |
|-------------|--|---|--|---------------------------------|
| HSEC 105 | 12,0 | 4,0 | 2,6 | 40,0 |
| HSEC 110 | 14,0 | 5,0 | 2,2 | 45,0 |
| HSEC 115 | 20,0 | 6,0 | 2,8 | 55,0 |
| HSEC 120 | 25,0 | 8,5 | 2,8 | 68,0 |
| HSEC 130 | 35,0 | 16,0 | 3,3 | 90,0 |
| HSEC 135 | 40,0 | 16,0 | 3,3 | 83,0 |
| HSEC 140 | 55,0 | 26,0 | 3,5 | 103,0 |
| HSEC 150 | 75,0 | 36,0 | 4,0 | 120,0 |
| HSEC 160 | 100,0 | 52,0 | 4,0 | 140,0 |
| HSEC 170 | 120,0 | 60,0 | 4,0 | 150,0 |
| HSEC 180 | 145,0 | 60,0 | 4,0 | 150,0 |
| HSEC 190 | 160,0 | 80,0 | 4,0 | 150,0 |
| HSEC 110L | 14,0 | 5,0 | 2,2 | 55,0 |
| HSEC 130L | 40,0 | 15,0 | 3,3 | 90,0 |
| HSEC 140L | 55,0 | 23,0 | 3,8 | 140,0 |
| HSEC 145L | 62,0 | 23,0 | 3,8 | 140,0 |
| HSEC 150L | 75,0 | 36,0 | 4,0 | 150,0 |
| HSEC 150XL | 75,0 | 36,0 | 4,2 | 170,0 |
| HSEC 160L | 100,0 | 47,0 | 4,0 | 155,0 |
| HCEC 120 | 25,0 | 8,5 | 2,8 | 68,0 |
| HCEC 130 | 42,0 | 15,0 | 3,3 | 110,0 |
| HCEC 140 | 55,0 | 23,0 | 3,8 | 140,0 |
| HCEC 145 | 62,0 | 23,0 | 3,8 | 140,0 |
| HCEC 150 | 75,0 | 32,0 | 4,0 | 150,0 |
| HCEC 150L | 75,0 | 36,0 | 4,2 | 170,0 |
| HCEC 160 | 105,0 | 45,0 | 4,0 | 150,0 |